






AIRMASTER OPTIONAL SYSTEM ACCESSORIES

<p>AKS GS02 (optional)</p>	<p>Differential Pressure Indicator Displays the level of saturation of the filter element. Shows accurate pressure drop and maximizes operational efficiency Max. Temp. 65°C Max. Pressure 12 bar</p>		<p>AKS TH03 (optional)</p>	<p>Solenoid Valve Timed Drain With a timer installed on a solenoid valve, the equipment ensures the time delay and interval of the discharge. Max. Temp. 65°C Max. Press: 12 bar</p>	
<p>AKS TH01 (optional)</p>	<p>Plastic Auto Float Drain Discharges accumulated condensate, contamination and oil via floating drain system. Max. Temp. 65°C Max. Pressure 12 bar</p>		<p>AKS TH04 (optional)</p>	<p>Stainless Steel Auto Float Drain Discharges accumulated condensate, contamination and oil via floating drain system. Max. Temp. 65°C Max. Pressure 12 bar</p>	
<p>AKS TH02 (optional)</p>	<p>External Auto Float Drain Best for fitting on air tanks, air dryers and filters. Discharges accumulated condensate, contamination and oil via floating drain system. Max. Temp. 65°C Max Press: 12 bar.</p>		<p>AKS TH05 (optional)</p>	<p>External Auto Float Drain Best for fitting on air tanks, air dryers and filters. Discharges accumulated condensate, contamination and oil via floating drain system. Max. Temp. 65°C Max Press: 12 bar.</p>	